

Sizes and measurements

PSI SEALING

| PVC Ø (outside diameter) | PVC Ø (inside diameter) | Inside range PSI plug Ø (inside diameter) |
|------------------------------------|-----------------------------------|---|
| 40 | 33.6 | 0 + van 05 t/m 20 |
| 50 | 43.6 | 0 + van 05 t/m 29 |
| 75 | 68.6 | 0 + van 20 t/m 52 |
| 110 | 103.6 | 0 + 25 + van 30 t/m 76 |
| 125 | 118.6 | 0 + 28 + 46 + 52 + van 60 t/m 94 |
| 160 | 152 | 0 + 62 + van 86 t/m 126 |
| 200 | 190.2 | 0 + 110 + 160 + van 124 t/m 152 |
| 250 | 237.6 | van 150 t/m 182 |

| DIN Ø (outside diameter) | DIN Ø (inside diameter) | Inside range PSI plug Ø (inside diameter) |
|------------------------------------|-----------------------------------|---|
| 42,4 | 37.2 | 0 + from 05 to 17 |
| 60,3 | 54.5 | 0 + from 15 to 35 |
| 88,9 | 82.5 | 0 + from 30 to 62 |
| 114,3 | 107.1 | 0 + from 50 to 84 |
| 139,7 | 131.7 | 0 + from 70 to 92 |
| 168,3 | 159.3 | 0 + from 80 to 126 |
| 219,1 | 207.3 | 0 + from 122 to 164 |
| 273 | 260.4 | from 150 to 202 |

| DH-AP Ø (outside diameter) | DH-AP Ø (inside diameter) | Inside range PSI plug Ø (inside diameter) |
|--------------------------------------|-------------------------------------|---|
| 35 | 35 | 0 + from 05 to 16 |
| 40 | 40 | 0 + from 05 to 23 |
| 50 | 50 | 0 + from 05 to 33 |
| 60 | 60 | 0 + from 20 to 42 |
| 70 | 70 | 0 + from 22 to 52 |
| 80 | 80 | 0 + from 30 to 58 |
| 90 | 90 | 0 + from 30 to 62 |
| 100 | 100 | 0 + from 30 to 66 |
| 110 | 110 | 0 + from 19 to 76 |
| 125 | 125 | 0 + from 40 to 92 |
| 150 | 150 | 0 + from 60 to 126 |
| 200 | 200 | 0 + 110 + 116 + 166 + from 124 to 162 |
| 250 | 250 | from 150 to 202 |

| ASTM Ø (outside diameter) | ASTM Ø (inside diameter) | Inside range PSI plug Ø (inside diameter) |
|-------------------------------------|------------------------------------|---|
| 60,3 | 52.5 | 0 + from 15 to 33 |
| 88,9 | 77.9 | 0 + from 20 to 50 |
| 114,3 | 102.3 | 0 + from 30 to 62 |
| 141,3 | 128.1 | 0 + from 50 to 90 |
| 168,3 | 154.1 | 0 + from 60 to 120 |
| 219,1 | 202.7 | 0 + 110 + from 124 to 160 |
| 273 | 254.4 | 114 + from 150 to 200 |